


## 24(W)×7 rotation resistant



24(W)×7

Nominal rope diameter	Approx. weight	Minimum breaking load			
		Rope grades, MPa			
		1570	1770	1960	2160
mm	kg/100m	kN	kN	kN	kN
8	29.4	36.2	40.8	45.2	48.4
9	37.3	45.8	51.6	57.2	61.2
10	46.0	56.5	63.7	70.6	75.6
11	55.7	68.4	77.1	85.4	91.5
12	66.2	81.4	91.8	102	109
13	77.7	95.5	108	119	128
14	90.2	111	125	138	148
16	118	145	163	181	194
18	149	183	206	229	245
20	184	226	255	282	302
22	223	274	308	342	366
24	265	326	367	406	435
26	311	382	431	477	511
28	361	443	500	553	593
30	414	509	573	635	680
32	471	579	652	723	774
36	596	732	826	914	980
40	736	904	1020	1130	1210
44	891	1090	1230	1370	1460
48	1060	1300	1470	1630	1740
52	1240	1530	1720	1910	2040
56	1440	1770	2000	2210	2370
60	1660	2030	2290	2540	2720

1 Total minimum breaking force of wire rope = Minimum breaking force x 1.287

# LEADER OF ELEVATOR & CRANE WIRE ROPES

Jiangsu Safety Wire Rope Co., Ltd. was established in June 2005, with a registered capital of 34 million USD, and 582 employees. We went public on Shanghai Stock Exchange in China on March 31, 2016 with the stock code: 603028. The factory covers an area of 102,000 square meters and has an annual output of 80,000 tons of steel wire ropes. Our market share & industry rankings for elevator wire ropes are among the top 3 in China.